

ALFATEK PREMIUM**Desincrustate and remover of residues of oil and heavy greases**

It is a degreasing industrial chemical biodegradable designed for heavy cleaning tasks.

It is capable of removing fuel oil, petroleum, grease, oil, tallow, wax, soot, dyes, resins, mold, and many other undesirable buildups.

It quickly infiltrates the layers of grease and other deposits and emulsifies them in the aqueous solution for an easy removal.

It does not contain kerosene, naphtha, kaolin, carbon tetrachloride or benzene.

It is very safe; it is not toxic, because it is not inflammable.

Where to Use

To clean and degrease industrial machinery and equipment (not electronic), parts, tools, etc.

To clean and degrease drilling equipment.

To clean concrete floors, steel and other materials.

To clean tanks of diesel, oils, petroleum and derivatives.

For descaling inside and out auto-tanque, buque-tanque and marine transport equipment.

ALFATEK PREMIUM it is a product with extraordinary qualities that help to optimize the processes of cleaning and industrial maintenance.

How to Use

This product is a concentrate that is diluted in water or diesel for greater effectiveness; although the dilution of this removes the biodegradable feature.

For greater effectiveness; use neoprene or latex gloves, filter masks and safety equipment.

Dilution:

The maximum recommended dilution is 1 liter of water or diesel by 4 of ALFATEK PREMIUM.

Cleaning with steam:

For very light tasks and application of steam we recommend a maximum of 10 liters of water dilution by 5 liters of ALFATEK PREMIUM.

Special features:

Manufacture on 100% biodegradable base.

Not concentrate in aquatic organisms.

Their degradation time is from 7 to 15 days.